

CREATIVE EFFECT PRODUCT GROUP

NIPPON PAINT GOLDY

PRODUCT DESCRIPTION

Acrylic emulsion-based, gloss, metallic-finish, decorative top-coat interior and exterior paint with gold foil appearance.

SPECIFICATIONS

Ready to use.

Easy-to-apply.

APPLICATION

The surface to be applied with Nippon Paint Goldy must be textured, stable, dry and self-supporting.

If it is to be applied on surfaces with old paint, the required surface preparation should be carried out with any desired grain, silicon or mineral coat or textured wallpaper.

A primer must be applied on the surfaces with old textures. For application on a surface with a color which matches the top coat, wait for 4 hours between coats and apply in 2 coats. For applications on a white surface, wait for 4 hours between coats and apply in three coats.

Avoid applying Nippon Paint Goldy on smooth substrates as much as possible. After preparing the substrate as required, apply on grain, acrylic or mineral based coats, paintable wall papers, decorative corner profiles, layer moldings, plasterboard and styrofoam-board type of textured surfaces.

Our products should be applied on substructure surfaces that are built in line with General Construction Specifications dated 30.06.2007 and with No. 26568.

EXTERIOR APPLICATION

The appearance, sheen and color of the product may vary according to the type and color of the material used for the surface. For surfaces to be painted for the first time and previously painted surfaces, prepare the surface as required with a textured base coat, which closely matches the final coat color.

If the application surface is textured, then the final coat must completely painted with a suitable DS E-20, DE-125 color. (DS E-20, DE-125 colors matching the top coat are listed on Nippon Paint Duchesse Satin Exterior color card). Apply the paint with a roller for exterior surfaces.

In order to prevent problems that arise from early drying; the paint should not be applied in direct sunlight, wind or other negative climate conditions. Tape the edges of the application surface with the masking tape. Finishing comb should be downwards and apply in 2- 3 coats and pay attention to the required resting time between coats.

The area should not be narrowed with layer moldings, joint gaps etc. on wide areas such as blind facades.

INTERIOR APPLICATION (on wall coating)

The appearance, sheen and color of the product may vary according to the type and color of the material used for the surface. Smooth the surface, apply homogeneously and evenly a rich amount using a coral roller for thick textured wallpapers and a satin roller for fine textured wallpapers.

Cut the coating dry and 10cm larger than the wall dimension depending on the texture, and start fixing by leaving 5cm from the top. Ensure the coating is perpendicular to the wall while fixing it. Fix the second coat by aligning the patterns at line zero without overlapping on the first coat. Remove the excess air with a trowel.

While applying Nippon Paint Goldy on the wall coating, it is recommended to apply a primer to the surface beneath in the same shade as Nippon Paint Goldy in order to obtain full coverage and a bright look. After the application of the primer, tape the edges of the application surface with the masking tape.

Use a satin roller. Comb downwards and apply as 2-3 coats waiting between coats as specified. Optionally, grain, silicone and mineral coating products can also be used for the preparation of the interior surface.

TECHNICAL SPECIFICATIONS

Brightness 72.33 gloss

Density: 1.05 ± 0.05 g/ml

THINNING

Ready to use. Do not thin.

DRYING TIME (at 20°C, 65% RH)

First drying: 45 minutes Final dry: 24 hours (drying time may increase at higher relative humidity and lower temperature)

CONSUMPTION

80-110 ml/m² in a single coat depending on the type, absorption and structure of the application surface. 1 Liter of paint covers a 9- 12 m² space with one coat. Perform a controlled sample run to estimate the precise consumption amount.

STORAGE

It can be stored in its unopened package for 3 years, in a cool and dry place, away from frost and direct sunlight. Close the lid air-tight immediately after application.

PACKAGE

0.6 LT

This technical sheet is prepared based on laboratory data at normal conditions. Consult technical personnel for details that are not provided hereinabove. Otherwise, the manufacturing company cannot be held responsible for failures that may arise due to lack of knowledge. Our company reserves the right to change the information provided hereunder.

Where necessary, please refer to Material Safety Data Sheets for more information on health, safety and handling risks, and precautions associated with the products.

This product is manufactured by Betek A.Ş. with certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002.